



ENCARDIO RITE

REFLECTIVE TARGET

MODEL ERT-10/20 SERIES

INTRODUCTION

Encardio-rite reflective targets are designed to suit a wide variety of surveying applications. They are used extensively for measurement of deformation during tunneling and subway construction, for monitoring bridges, dams, slopes and building structures.

DESCRIPTION

Model ERT-10B Bireflex target

Model ERT-10B bireflex target consists of reflector mounted on a robust frame. The target has reflectors on both the sides and is mounted on a universal joint such that it can be oriented in any direction as required. The target has a small centre hole to allow precise targeting.



The bireflex target is made of high performance materials and precise manufacturing processes. The target is thus, interchangeable.

Model ERT-10P Prism target

Model ERT-10P prism target consist of a mini prism mounted on a robust frame. This is also mounted on a universal joint such that it can be oriented in any direction as required. The target is interchangeable.

Optional components

The optional components which can be ordered separately with both model ERT-10B and ERT-10P include convergence bolts with

FEATURES

- ◆ Precise, rugged, interchangeable and low cost
- ◆ Compact construction
- ◆ Easy installation
- ◆ Robust frame and bolts with firm grip
- ◆ Precise surveying application where total stations are used

APPLICATIONS

- ◆ Measurement of deformation in tunnel
- ◆ Measurement of deformation in subway construction
- ◆ Monitoring of dams, bridges and slopes
- ◆ Monitoring of building structures
- ◆ Surveying works

protective cap and adaptor with reference break-off point. The break-off point adaptor is required to mount the target on the convergence bolts.

Model ERT-20P-M1 Mini prism target

Model ERT-20P-M1 mini prism consists of a prism mounted on a swivel bracket. This target is not interchangeable



SPECIFICATIONS

ERT-10B Bireflex target (Part # 11-05150)

Measuring range	Approximately 12 m to 140 m
Manufacturing accuracy	± 0.1 mm
Material	Reflector support is plastic, mounted on universal joints with reflective foil on both sides

ERT-20P-M1 Mini prism target (Part # 11-06035)

Measuring range	Approximately 0.3 m to 600 m
Addition constant	+17.5 mm

ERT-10P Prism target (Part # 11-06032)

Measuring range	Approximately 0.3 m to 600 m
Manufacturing accuracy	± 0.1 mm
Addition constant	+17.5 mm
Material	Reflector support is plastic, mounted on universal joints

Convergence bolts (Part # 11-05152)

Material	Galvanised steel Fe 415 dia 20 mm [IS:1786]; stainless steel threaded stud, pipe thread 3/8"
Length	250 mm standard

Protective cap (Part # 11-05045)

Material	Red polyvinyl chloride
----------	------------------------

Break-off point (Part # 11-05133)

Material	Plastic
----------	---------

All specifications are subject to change without prior notice.

ENCARDIO-RITE ELECTRONICS PVT. LTD.

A-7 Industrial Estate, Talkatora Road, Lucknow, UP-226011, India

Tel +91 (522) 2661044, 2661040 Fax +91 (522) 2661043 E-mail sales@encardio.com

Visit us at: www.encardio.com

DATA SHEET 1199-06R1